



DDFCUC010

Fan Coil Unit Controller

Direct control of air conditioning


The Philips Dynalite DDFCUC010 is a fan coil unit controller designed for direct connection to components commonly found in air conditioning systems.

DDFCUC010

Direct control of air conditioning

- **0-10 V outputs** – Provided for controlling hot and cold-water valves.
- **Relay outputs** – Provided for driving fan motors.
- **High capacity relay** – Provided for use with electrical heaters or power outlet switching.
- **Inputs for resistive temperature sensors** – Allows the device to use data from a local temperature sensor or a networked temperature sensor, such as an Antumbra user interface.
- **Programmable auxiliary inputs** – Provided for use with peripheral devices including smoke detectors, motion detectors, window open/close sensors, airflow detectors, drip trays, dirty air filters and hot water on cold valve.
- **Networkable** – Can be networked with other equipment including Philips Dynalite user interfaces, via an on-board RS-485 DyNet port.

Dimensions



Specifications

Due to continuous improvements and innovations, specifications may change without notice.



DDFCUC010

Fan Coil Unit Controller

Electrical

Supply Type	Single-phase
Supply Voltage	230 VAC ($\pm 14\%$)
Supply Current	10 A
Water Valve Control Outputs	Floating: 2 x 0-10 V @ 10 mA (max) Valve actuator coil: 2 x 24 VAC @ 4 VA (max)
Fan Control Output	1 x 230 VAC @ 10 A (Three-way selectable relay - High, Medium, Low)
Electric Heater Output	1 x 230 VAC @ 16 A
DyNet DC Output Voltage	12 VDC
DyNet DC Output Current	120 mA
IEC Overvoltage Category	III

Control

Communication Ports	2 x RS-485
Supported Protocols	DyNet
Dry Contact Inputs	3
Temperature Sensor Inputs*	1 x 20 K NTC
User Controls	1 x service switch
Indicators	1 x service LED

Physical

Dimensions (H x W x D)	95 x 211 x 75 mm (3.70 x 8.31 x 2.95 in)
Packed Weight	0.8 kg (1.76 lb)
Construction	Polycarbonate DIN-rail case (12 unit)
Communication Ports	2 x RJ12 5 x screw terminal
Communication Terminal Conductor Size	2.5 mm ² (#12 AWG) (max)
Control Outputs	11 x screw terminal
Dry Contact Inputs	6 x screw terminal
Maximum Dry Contact Cable Length	20 m
Temperature Sensor Input	2 x screw terminal
Supply Terminals	5 x screw terminal
Input/Output/Supply Terminal Conductor Size	4 mm ² (#11 AWG) (max)

Environment

Operating Temperature	-0° to 50°C ambient (32° to 122°F)
Storage/Transport Temperature	-25° to 70°C ambient (-13° to 158°F)
Humidity	0 to 90% non-condensing
IEC Pollution Degree	III


Compliance

Certification	CE, RCM, RoHS
---------------	---------------

* Networked temperature sensors also supported.



Electrical



Ordering Code

Product

DDFCUC010

Philips 12NC

913703081909



© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.